

Screws

► Direct fixing screws, handle fixing screws

Shallow countersunk head



- Shallow countersunk head
- Pozidrive screw
- Steel, galvanised

Dimensions mm	Order no.	PU
ø 4.5 x 13.5	0 073 751	200 ea.
ø 6.3 x 10.5	0 051 264	200 ea.
ø 6.3 x 11	0 047 451	200 ea.
ø 6.3 x 12.5	0 073 752	200 ea.
ø 6.3 x 14	0 051 265	200 ea.
ø 6.3 x 15	0 073 889	200 ea.
ø 6.3 x 18	0 052 799	200 ea.

Deep countersunk head



- Deep countersunk head
- Pozidrive screw
- Steel, galvanised

Dimensions mm	Order no.	PU
ø 6.3 x 10.5	0 073 890	200 ea.
ø 6.3 x 14	0 047 452	200 ea.

Handle fixing screws



- M4 thread
- Cross recessed head and double slot
- Steel, galvanised

Length mm	Order no.	PU
12	0 071 544	50 ea.
14	0 071 545	50 ea.
16	0 071 546	50 ea.
18	0 071 547	50 ea.
20	0 071 548	50 ea.
22	0 071 549	50 ea.
24	0 071 555	50 ea.
26	0 071 556	50 ea.
28	0 071 557	50 ea.
30	0 071 558	50 ea.
32	0 071 559	50 ea.
34	0 071 560	50 ea.
36	0 071 561	50 ea.
38	0 071 562	50 ea.
40	0 071 563	50 ea.
42	0 071 855	50 ea.
45	0 071 856	50 ea.