

Fast assembly concealed hinge with integrated Silent System

- ▶ Sensys 8645i
- ▶ Opening angle 110°, packaging unit 50 ea.



- ▶ Concealed hinge with clip on installation and integrated Silent System
- ▶ Quality classification under EN 15570, Level 3
- ▶ For door thickness 15 - 24 mm
- ▶ Cup diameter 35 mm
- ▶ Cup depth 12.8 mm
- ▶ Integrated +/- 2 mm overlay adjustment
- ▶ Integrated depth adjustment + 3 mm / - 2 mm
- ▶ Height adjustment at mounting plate
- ▶ Hinge arm material: steel, nickel plated
- ▶ Hinge cup material: steel, nickel plated

Sensys 8645i, opening angle 110°

Cup assembly	Drilling pattern	Mounting drilling ø x T mm	full overlay	half overlay	inset	PU
			Base B 12.5 mm	Base B 3 mm	Base B -4 mm	
For screwing on TH 52		-	9 073 605	9 073 606	9 073 607	1/50 ea.
For pressing in TH 53		ø 10 x 11	9 073 608	9 073 609	9 073 610	1/50 ea.
Flash fast assembly TH 54		ø 10 x 11	9 073 611	9 073 612	9 073 613	1/50 ea.
Fix fast assembly THS 55		ø 10 x 6	9 073 614	9 073 615	9 073 616	1/50 ea.
For screwing on TB 52		-	9 073 617	9 073 618	9 073 619	1/50 ea.
For pressing in TB 53		ø 8 x 11	9 073 620	9 073 621	9 073 622	1/50 ea.
Flash fast assembly TB 54		ø 8 x 11	9 073 623	9 073 624	9 073 625	1/50 ea.
Fix fast assembly TB 55		ø 8 x 6	9 073 626	9 073 627	9 073 628	1/50 ea.