

Fast assembly concealed hinge without integrated Silent System

- ▶ Sensys 8645
- ▶ Opening angle 110°



- ▶ Concealed hinge with clip on installation without integrated Silent System
- ▶ Quality classification under EN 15570, Level 3
- ▶ For door thickness 15 - 24 mm
- ▶ Cup diameter 35 mm
- ▶ Cup depth 12.8 mm
- ▶ Integrated +/- 2 mm overlay adjustment
- ▶ Integrated depth adjustment + 3 mm / - 2 mm
- ▶ Height adjustment at mounting plate
- ▶ Hinge arm material: steel, nickel plated
- ▶ Hinge cup material: steel, nickel plated

Sensys 8645, opening angle 110°

Cup assembly	Drilling pattern	Mounting drilling ø x T mm	full overlay	half overlay	inset	PU
			Base B 12.5 mm	Base B 3 mm	Base B -4 mm	
For screwing on TH 52		-	9 073 638	9 073 639	9 073 640	1/50 ea.
For pressing in TH 53		ø 10 x 11	9 073 641	9 073 642	9 073 643	1/50 ea.
Fix fast assembly THS 55		ø 10 x 6	9 073 644	9 073 645	9 073 646	1/50 ea.
For screwing on TB 52		-	9 073 647	9 073 648	9 073 649	1/50 ea.
For pressing in TB 53		ø 8 x 11	9 073 650	9 073 651	9 073 652	1/50 ea.
Fix fast assembly TB 55		ø 8 x 6	9 073 653	9 073 654	9 073 655	1/50 ea.