






Fast assembly concealed hinge with integrated Silent System

- ▶ Sensys 8631i for thick doors
- ▶ Opening angle 95°



- ▶ Concealed hinge with clip on installation and integrated Silent System
- ▶ Quality classification under EN 15570, Level 2
- ▶ For door thickness of 15 – 32 mm
- ▶ Cup diameter 35 mm
- ▶ Cup depth 12.8 mm
- ▶ Integrated overlay adjustment + 2 mm / - 2 mm
- ▶ Integrated depth adjustment + 3 mm / - 2 mm
- ▶ Height adjustment at mounting plate
- ▶ Hinge arm material: steel nickel plated
- ▶ Hinge cup material: steel nickel plated

Sensys 8631i, opening angle 95°

| Cup assembly | Drilling pattern | Mounting drilling ø x T mm | full overlay | half overlay | inset | PU |
|------------------------------|---|-------------------------------|---|---|---|----------|
| | | |  |  |  | |
| For screwing on TH 52 |  | - | 9 091 400 | 9 091 410 | 9 091 420 | 1/50 ea. |
| For pressing in TH 53 | | ø 10 x 11 | 9 091 401 | 9 091 411 | 9 091 421 | 1/50 ea. |
| Flash fast assembly TH 54 | | ø 10 x 11 | 9 091 402 | 9 091 412 | 9 091 422 | 1/50 ea. |
| For screwing on TB 52 |  | - | 9 091 430 | 9 091 440 | 9 091 450 | 1/50 ea. |
| For pressing in TB 53 | | ø 8 x 11 | 9 091 431 | 9 091 441 | 9 091 451 | 1/50 ea. |
| Flash fast assembly TB 54 | | ø 8 x 11 | 9 091 432 | 9 091 442 | 9 091 452 | 1/50 ea. |