






# Fast assembly concealed hinge without integrated Silent System

- ▶ Sensys 8631 for thick doors
- ▶ Opening angle 95°



- ▶ Concealed hinge with clip on installation without integrated Silent System
- ▶ Quality classification under EN 15570, Level 2
- ▶ For door thickness of 15 – 32 mm
- ▶ Cup diameter 35 mm
- ▶ Cup depth 12.8 mm
- ▶ Integrated overlay adjustment + 2 mm / - 2 mm
- ▶ Integrated depth adjustment + 3 mm / - 2 mm
- ▶ Height adjustment at mounting plate
- ▶ Hinge arm material: steel nickel plated
- ▶ Hinge cup material: steel nickel plated

## Sensys 8631, opening angle 95°

Cup assembly	Drilling pattern	Mounting drilling ø x T mm	full overlay	half overlay	inset	PU
						
For screwing on TH 52		-	<b>9 091 490</b>	<b>9 091 500</b>	<b>9 091 510</b>	1/50 ea.
For pressing in TH 53		ø 10 x 11	<b>9 091 491</b>	<b>9 091 501</b>	<b>9 091 511</b>	1/50 ea.
For screwing on TB 52		-	<b>9 091 520</b>	<b>9 091 530</b>	<b>9 091 540</b>	1/50 ea.
For pressing in TB 53		ø 8 x 11	<b>9 091 521</b>	<b>9 091 531</b>	<b>9 091 541</b>	1/50 ea.